

Oscar Jade Zero 0W16 is a very high performance, **ultra-low viscosity** fluid, **fully synthetic** lubricant for gasoline and **hybrid** engines, including the ones complying with **ILSAC GF-6B** standard. Oscar Jade Zero 0W16 is formulated to help to increase engine efficiency and improve fuel economy benefits, while providing outstanding overall engine protection.

APPLICATION

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.

PROPERTIES

- **Fuel Economy**
- **Biofuel Compatible**
- **For Hybrid engines**

PERFORMANCE LEVELS

Meets and exceeds: API SP and RC; API SN and RC; API SN Plus and RC; ILSAC GF-6B; GM dexos1™ Gen 2

TYPICAL PROPERTIES

PARAMETERS	TEST METHOD	UNIT	OSCAR JADE ZERO 0W16
Viscosity Grade			0W16
Density @ 15°C	ASTM D1298	kg/l	0.838
Viscosity @ 100°C	ASTM D445	cSt	7.2
Cold Crank Simulator	ASTM D5293	cP	6,200 @ -35 °C
HTHS Viscosity 150°C	-	mPa.s	2.7
Pour Point	ASTM D97	°C	-50
Flash Point	ASTM D92	°C	230
Total Base Number (TBN)	ASTM D2896	KOH/g	8

The values shown above are typical values at the date of publication. Oscar Lubricants reserves the right to change these typical values without prior notice

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.oscarlubricants.com